



THE EASY CHOICE WHEN LUXURY, PERFORMANCE AND VALUE MATTER.

Whether picking up VIPs at a private airport, or escorting guests on a factory tour, our four- and six-seat Concierge models will impress even the most discerning passengers. With a smooth, quiet ride, and the widest, most comfortable seats in the industry, these vehicles provide a truly first-class experience.



SPECIFICATIONS

4 PASSENGER QUIETECH EFI

DIMENSIONS

OVERALL LENGTH	127.2 in (323 cm)
OVERALL WIDTH	47.2 in (120 cm)
OVERALL HEIGHT (no suntop)	48.8 in (124 cm)
WHEEL BASE	98.0 in (249 cm)
TREAD (FRONT)	34.6 in (88 cm)
TREAD (REAR)	38.2 in (97 cm)
MINIMUM GROUND CLEARANCE	5.9 in (15 cm)
DRY WEIGHT WITH SUNTOP	441.6 kg
FLOOR BOARD HEIGHT	13.4 in (34 cm)

GENERAL

FUEL TANK CAPACITY	22 liters (5.8 gallons)
TIRE SIZE	205/65-10 4PLY
SEATING CAPACITY	4 persons
AVAILABLE MODEL COLORS	Glacier Metallic: Bluestone, Rich Brown, Moonstone, Sandstone, Onyx, Aqua Blue, Jasper
AVAILABLE SEAT COLORS	Standard: Stone Optional: Black
AVAILABLE SUNTOP COLORS	Stone, Black , White
WARRANTY	Standard 2 year limited vehicle warranty

ENGINE

TYPE OF ENGINE	Yamaha-built 357cc, low-emission single cylinder 60° incline OHV
LUBRICATION SYSTEM	Splash-style positive oil lubrication
OIL CAPACITY (L)	1 U.S. quart (1 Liter, 1000cc)
TYPE OF AIR CLEANER	Two-stage, urethane-foam pre-cleaner, and high- capacity pleated paper cartridge
COOLING SYSTEM	Forced Air
FUEL SYSTEM	Electronic Fuel Injection
STARTING SYSTEM	Starter Generator with pedal start

CHASSIS

FRAME	HybriCore™ Chassis features a robotic welded automotive ladder-style steel frame protected with a multi-step full-immersion phosphate treatment, electro-deposition epoxy-based coating, and an electrostatic applied polyester/ urethane powder topcoat
BODY	Mold-in Polypropylene for Glacier Color. Custom- formulated thermoplastic olefin painted with a two-part top coat of high-luster automotive- grade polyurethane
STEERING	Self-compensating double reduction helical rack-and-pinion
FRONT SUSPENSION	Tru-Trak II™ fully independent automotive-style strut suspension
REAR SUSPENSION	Fully independent automotive-style strut suspension
BRAKE SYSTEM (MAIN)	Self-adjusting mechanical, rear wheel drum brakes
BUMPERS	Front and rear 5 mph energy-absorbing bumpers

PERFORMANCE

MAXIMUM SPEED	19 mph (31 km/h)
MINIMUM TURNING RADIUS	14.4 ft (4.4 m)

4 PASSENGER POWERTECH AC

DIMENSIONS

OVERALL LENGTH	127.2 in (323 cm)
OVERALL WIDTH	47.2 in (120 cm)
OVERALL HEIGHT (no suntop)	48.4 in (123 cm)
WHEEL BASE	98.0 in (249 cm)
TREAD (FRONT)	34.6 in (88 cm)
TREAD (REAR)	38.2 in (97 cm)
MINIMUM GROUND CLEARANCE	5.5 in (14 cm)
WEIGHT WITH SUNTOP AND TROJAN T-875 BATTERIES	563 kg
FLOOR BOARD HEIGHT	13.0 in (33 cm)

GENERAL

TIRE SIZE	205/65-10 4PLY
SEATING CAPACITY	4 persons
AVAILABLE MODEL COLORS	Glacier Metallic: Bluestone, Rich Brown, Moonstone, Sandstone, Onyx, Aqua Blue, Jasper
AVAILABLE SEAT COLORS	Standard: Stone Optional: Black
AVAILABLE SUNTOP COLORS	Stone, Black , White
WARRANTY	Standard 2 year limited vehicle warranty

MOTOR / DRIVE TRAIN / POWER SUPPLY

MOTOR	48-Volt AC
OUTPUT RATING	6.7 hp (5.0 kW) for 60 minutes
MOTOR CONTROL UNIT	NEOS 350 amp AC controller by Toyota Industries Corporation
BATTERIES	Standard: Six 8-volt Trojan T-875 Batteries, Optional: Eight 6-volt Trojan T-105 Batteries

CHASSIS

FRAME	HybriCore™ Chassis features a robotic welded automotive ladder-style steel frame protected with a multi-step full-immersion phosphate treatment, electro-deposition epoxy-based coating, and an electrostatic applied polyester/ urethane powder topcoat
BODY	Mold-in Polypropylene for Glacier Color. Custom- formulated thermoplastic olefin painted with a two-part top coat of high-luster automotive- grade polyurethane
STEERING	Self-compensating double reduction helical rack-and-pinion
FRONT SUSPENSION	Tru-Trak II™ fully independent automotive-style strut suspension
REAR SUSPENSION	Fully independent automotive-style strut suspension
BRAKES	Self-adjusting mechanical, rear wheel drum brakes
BUMPERS	Front and rear 5 mph energy-absorbing bumpers

PERFORMANCE

MAXIMUM SPEED	19 mph (31 km/h)
MINIMUM TURNING RADIUS	14.4 ft (4.4 m)